

Ready-toconnect prefabricated showers

Prefabricated shower range **2014**











Karl Grumbach GmbH & Co. KG · Breitteilsweg 3 · 35581 Wetzlar Telephone (+49 64 41) 97 72 0 · Telefax (0049 64 41) 97 72-20 www.grumbach.net · grumbach@grumbach.net



Grumbach

...Innovation, Competence, Experience



Contents

- 4-5 Prefabricated showers
 STANDARD and SOUVERÄN
 - 6 Prefabricated shower SENIOR
 - 7 Technical data for the pre- fabricated showers STANDARD, SOUVERÄN and SENIOR
- 8-9 Prefabricated showers Model versions and prices
- 10 Grumbach representatives

Grumbach prefabricated showers

The family business **Grumbach** with its seat in Wetzlar-Münchholzhausen is currently one of the leading suppliers of prefabricated showers in Germany.

Simply position it, connect it up and shower -

all of the **Grumbach** prefabricated showers (also called complete showers) function in this way.

The current range consists of a wide spectrum of models starting from the inexpensive standard shower to the accommodating senior shower all the way to the comfortable multifunctional shower.

They are equally suitable for hotels, guesthouses, care homes or sanitary areas in commercial and industrial properties.





Grumbach Prefabricated showers

Standard, convenient or comfortable: Grumbach has the right prefabricated shower for every situation.



Prefabricated shower SOUVERÄN

with real glass sliding folding door, 18 l hot water tank (32 cm entry) and wastewater pump (Art.-No. 330.88.N, 901, 921)

Grumbach Prefabricated showers

- 4 basic types with numerous configurtions
- quick and easy to assemble
- top price/performance ratio
- are made of high quality plastic (PS) and are complete and fitted to a high standard.
- They stand out due to the high level of price/performance ratio that means: clear, rational design proven technology and of course sensible prices.
- Prefabricated showers can be fitted in record time almost anywhere without any problems.
- You only need a warm, a cold and a wastewater connection. If there is no warm water connection the showers can be delivered with an integrated warm water tank. If there is no wastewater connection the prefabricated shower can be delivered with an integrated wastewater pump. The electric parts are accessible without the disassembly of the prefabricated shower.

Prefabricated shower variations:

Depending on the model. choose between

- 1 closed ceiling (normal version) or open ceiling (on request, at extra cost)
- 4 different ways to access
- 3 the shower tray size 80 x 80 or 90 x 90 cm
- O low entry (only 17 cm, or with the built-in warm water tank 32 cm
- Single walls or double walls with integrated soundproofing core
- integrated 18 I warm water tank (then 32 cm access) or separate 25 I warm water tank
- 7 total height 206 cm or total height 220 cm







Prefabricated shower STANDARD-with three part sliding door. (Art.-No. 130.88.N)



Prefabricated shower STANDARD PLUS with swinging doors made of artificial glass and wastewater pump (Art.-Nr. 210.88.N, 921)



Prefabricated shower SOUVERÄN with real glass sliding folding door, 18 I hot water tank (32 cm entry) and wastewater pump (Art.-No. 330.88.N, 901, 921)

■ Facilities and Features STANDARD and SOUVERÄN

Prefabricated shower STANDARD

- high quality plastic (PS) in white.
- completely fitted out with shower partition 2-handled single-hole fitting and shower set (hose, adjustable hand shower and soap dish)
- with single walls (4 mm thick) externally grained, inside smooth, with small step into the tray
- with split back wall for problem-free connection, even from the inside (for example, installation in a niche)
- with adjustable feet for simple positioning
- with base consisting of an ABS shower tray 80 x 80 and a stable PUR support
- · with closed ceiling
- with low entry 17 cm or normal entry 32cm (with integrated 18-liter hot water tank)
- with curtain, sliding folding door or 3-part real glass sliding door or with 2 solid swinging doors made of artificial glass

Prefabricated shower STANDARD PLUS

like STANDARD, but

- extra tall 220cm
- with sliding folding door, 3-part sliding door or with 2 solid swinging doors made of artificial glass

Prefabricated shower SOUVERÄN

like STANDARD PLUS, but

- with double walls (16mm thick), both internally and externally grained, without step and with soundproofing
- with 60mm assembly duct as wall covering
- available with 80 x 80 or 90 x 90cm shower tray
- With real glass sliding folding door, 3-part real glass sliding door or with 2 solid swinging doors made of artificial glass



Prefabricated showers STANDARD and SOUVERAN



Prefabricated shower SOUVERÄN

with three part real glass sliding door, shower tray 90 x 90 and low entry (17cm) (Art.-Nr. 330.99.N)





All necessary connections of the Grumbach prefabricated showers are pre-fitted - ideal for quick and simple installation.

fig.: Prefabricated shower SOUVERÄN with 18 I warm water tank and wastewater pump

Prefabricated shower SOUVERÄN

with three part real glass sliding door, shower tay 90 x 90 and low entry (17cm) (Art.-Nr. 330.99.N)

combined with

Washbasin wall (Art.-Nr. 950)



prefabricated shower SENIOR

... for seniors, or just because it's easier



Prefabricated shower SENIOR with access assistance and bench (Art.-No. 410.99.N, 960)



Prefabricated shower SENIOR

The Grumbach prefabricated shower SENIOR is equipped with the latest anodized, assymetrical swinging doors made of artificial glass.

Inside the shower cabinet, the bench and the thermostatic fitting provide a comfortable showering experience.

The low access height into the 90 x 90cm shower tray is only 17cm! Access can be made even easier by fitting a support rail. (Art.-Nr. 960)

Even the extra external 25 litre hot water tank can be fitted to the high quality Prefabricated shower SENIOR. In this case the shower is supplied with a single-lever mixer instead of a thermostatic fitting.



Technical data for the prefabricated showers STANDARD, SOUVERAN and SENIOR

Access and miscellaneous

Plastic curtain

"When simple is sufficient"



Swing doors made of artificial glass


The 2 swing doors made of artificial glass and anodised Aluminium frames are easy to maintain, stable and can be opened really wide. The swing doors lock with a strong magnet seal. wide. The swing doors lock with a strong magnet seal.



Real glass sliding folding door

New!


Aluminium, silver anodised with transparent toughened safety glass (TSG), made by Koralle, very high quality. Can be opened to the left or right, the full access width remains available.



3 part real glass sliding door

New!

Aluminium, silver anodised with transparent toughened safety glass (TSG), made by Koralle, very attractive design.



Equipped with the following taps

2-handed mixer, 18mm chrome plated wall pipe. High quality hose, adjustable shower head and soap dish.


2-hole wall fitting, chrome plated on request, at extra cost

one-handed mixer

(High pressure or low-pressure variation) on request, at extra cost

Equipment options

All showers also available with tank and pump.



■ Dimensions and data prefabricated showers

Mass (in cm)	STANDARD	STANDARD PLUS	STANDARD/ STANDARD PLUS with 18 I warm water tank	SOUVERÄN 80 x 80 cm	SOUVERÄN 80 x 80 cm with 18 I warm water tank	SOUVERÄN 90 x 90 cm*	SENIOR
B= Width	80	80	80	80	80	90	90
T=Depth	81	81	81	87	87	97	97
WT=Tray depth	79	79	79	79	79	89	89
H=Height	206	220	220	220	220	220	220
SH=Standing height	194	208	198	208	198	208	208
EH=Access height	17	17	32	17	32	17	17
AH=Drain height	7	7	15	7	15	7	7
AA=Fitting spacing	15,5	15,5	15,5	15,5	15,5	15,5	15,5

^{*} SOUVERÄN 90 x 90 cm with 18 I warm water tank it is not offered.



Prefabricated showers

					71.1
Model	Standard configuration	Access type	Order No.		/Unit
				80 x 80 cm	90 x 90 cm
-	Prefabricated shower STANDARD	Curtain	100.88.N	1105,-	
The state of the s	Dimensions 80 x 81 x 206 cm (W x D x H) High quality plactic (PS) in white	Artificial glass swinging	110.88.N	1275,-	
	High quality plastic (PS) in white. Completely fitted out with shower partition 2-handled	door			
	single-holed fitting and shower set (hose, adjustable	Real glass folding sliding	120.88.N	1585,-	
	hand shower and soap dish)	door			
	with single walls (4mm thick) externally grained, inside smooth; with small step in the tray	3 part real glass sliding	130.88.N	1610,-	
	with split back wall for problem free con- nection,	door			
	even from the inside, with adjustable feet for simple positioning				
	• with base consisting of an ABS shower tray 80 x 80				
	and a stable PUR support				
	with low entry 17 cm or normal entry the low version always has a closed ceiling				
	and tow version amayo has a closed centing				
1	Prefabricated shower	Artificial glass swinging	210.88.N	1440,-	
E P	STANDARD PLUS	door			
0 0	• Dimensions 80 x 81 x 220 cm (W xDx H)	Real glass folding sliding	220.88.N	1700,-	
22 (7)	• like STANDARD, but	door		·	
extra high 220 cm	extra tall 220cm with closed ceiling	3-tlg. Echtg3 part real	230.88.N	1725,-	
tra	with closed centing	glass sliding door		·	
6					
V					
^	Prefabricated shower SOUVERÄN	Artificial glass swinging	310.88.N	1550,-	
E .	• Dimensions: 80 x 87 x 220 cm or 90 x 97 x 220 cm	door	310.00.11	1550,-	
20 0	(W x D x H)	Real glass folding sliding	320.88.N	1895,-	
2	• like STANDARD, but	door	320.00.11	1033,-	
a high	 with double walls (16mm thick), both internally and ex- ternally grained, without step and with soundproofing 	3 part real glass sliding	330.88.N	1920,-	
extra high 220 cm	with 60mm assembly duct as wall covering	door	330.00.11	1320,	
	very stable construction!				
V		Artificial glass swinging	310 .99 .N		1740,-
		door			
		Real glass folding sliding	320 .99 .N		2060,-
		door			,
		3 part real glass sliding	330 .99 .N		2090,-
		door			,
1/4	Prefabricated shower SENIOR	plastic swinging door	410 .99 .N		2055,-
	• like Model SOUVERÄN, but				
1	• Dimensions: 90 x 97 x 220 cm (W xDx H)				
7	with double walls (18 mm thick), both internally and externally grained, without step and with sound-				
1	proofing core (10 mm thick); rear wall thickness 6 mm				
	• with 60mm assembly duct as wall covering				
	with bench (corner seat), with thermostat fitting and 2 shelves				
	• with low access (17cm)				
	• with 90 x 90cm shower tray -without access assistance and warm water tank				
	(available as optional extra, see page 9, Art.Nr. 960)				



Model variations and prices 2014

Accessories and ext	ra convigad	Order No.	Euro/Unit
Accessories and ext	i a services	Order No.	Lui 0/ Ollic
	25-Litre-hot water tank, low pressure • external Boiler, 2 kW • with covering made of white PS • ideal for prefabricated showers with low access • Can be fitted to the side of prefabricated shower STANDARD, SOUVERÄN or SENIOR or fitted to the wall • Dimensions: 29.5 x 28.5 x 106.5 cm	903	505,-
without illustration	18-Litre-hot water tank, low pressure • 2 kW, with thermostat	901	350,–
	Tank is fitted below the shower. Access height is therefore 32 cm and the total height 320 cm. Access assistance made of PS (Accessory for - prefabricated shower SENIOR) Consists of 2 hand rails and an 8cm access step. This makes access to the prefabricated shower Senior much easier.	960	120,-
E.	Washbasin wall For fitting to or on showers or as a separate component. The washbasin wall is white and comes complete with the sanitary components shown (mirror, lights, sockets with switch, 2 handed chrome-plated mixer and 2 corner valves). W = 78 cm, H = 220 cm (can be shortened)	950	1250,-
Pumps (are integrated	Wastewater pump 70 W, Delivery height 1.50 m, manual (only possible with high base/ normal access)	920	150,–
into the base of the shower)	Automatic wastewater pump 70 W, Delivery height 1.50 m	921	265,–
Very compact, low configuration!	Wastewater pump 170 W, Delivery height 2.50 m, manual incl. backflow valve (only possible with high base/ normal access)	922	239,–
Attention: It is forbidden to use this pump in any industrial or commercial purpose!	Automatic wastewater pump 170 W, Delivery height 2.50 m, incl. backflow valve	923	419,–
One handed mixer fittin	One handed mixer fitting, high pressure configuration	931	92,–
	One handed mixer fitting, low pressure configuration for tank	933	115,–
Thermostat fitting	Aunted hand shower thermostat in chrome, with temperature control and flow control, without fitting	932	187,–
Pressure hose	Easy to connect, 1m long, ½" connection	981	29,–
Reduction of the	Shortening STANDARD, STANDARD PLUS	940	112,–
total height	Shortening* SOUVERÄN, SENIOR	941	207,–
	*always possible in the casae of prefabricated showers with curtain and artificial glass swinging doors, in the case of real glass folding sliding doors or 3 part real glass sliding doors, only up to door-height. Further shortening for real glass versions on request.		





															I										
															ļ										
															ı										
									ı						i										
															Ī										
															H										
															ı										
															ı										
			Ħ												İ										
															ı										
															#	ш	ш	ш							
															ı										
															▋										
															#		ш	ш							
																									$\ $
										İ	Ħ														

